



# Safety Data Sheet

GLITSA LATITUDE FINISH

**PRODUCT NAME:** GLITSA LATITUDE FINISH (all sheens)  
**PRODUCT CODE:** 270122

**HMIS CODES:** H F R P  
 2\*0 0 X

===== SECTION I - MANUFACTURER IDENTIFICATION =====

**MANUFACTURER'S NAME:** Rudd Company, Inc.  
**ADDRESS:** 1141 N.W. 50th Street, Seattle WA 98107-5120  
**EMERGENCY PHONE:** Call Chemtrec 1-800-424-9300 (spill, leak, fire, accident)  
**INFORMATION PHONE:** 206-789-1000  
**NAME OF PREPARER:** Rudd Company, Inc. - Regulatory Department

===== SECTION II - HAZARDS IDENTIFICATION =====

**GHS CLASSIFICATION:**

Eye Irritation 2  
 Skin Irritation 2  
 Reproductive Toxicity 1B  
 Specific Target Organ Toxicity (Single Exposure) 3

**PICTOGRAM:**



**SIGNAL WORD:**

WARNING

**HAZARD STATEMENTS:**

May cause skin irritation. May cause eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child.

**PRECAUTIONARY STATEMENTS:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. **IF SWALLOWED:** Call a POISON CENTER or doctor/physician. Rinse mouth. **IF ON SKIN:** Wash with plenty of soap and water. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplemental first aid instructions on the label or in Section IV of the SDS). Rinse mouth. If eye irritation persists: Get medical advice/attention. Dispose of contents/container according to local and federal regulations.

===== SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @ TEMP		PERCENT
* n-METHYL-2-PYRROLIDONE	872-50-4			7-8
TRI-BUTYLETHYL PHOSPHATE	78-51-3			1-2
* TRIETHYLAMINE	121-44-8	54	68	1-2
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	13	77	1-2

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION IV - FIRST AID MEASURES =====

**GENERAL ADVICE:**

Have Material Safety Data Sheet available when calling Poison Control Center (1-800-222-1222) or physician; or when going to the emergency room.



**IF INHALED:**

Remove from exposure to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Get medical attention immediately.

**IN CASE OF SKIN CONTACT:**

Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash or clean thoroughly before reuse. Get medical attention if irritation persists.

**IN CASE OF EYE CONTACT:**

Immediately flush with plenty of water for 15 minutes, while lifting upper and lower eyelids. Get medical attention.

**IF SWALLOWED:**

DO NOT induce vomiting. Call Poison Control Center (1-800-222-1222) or physician immediately.

===== **SECTION V - FIREFIGHTING MEASURES** =====

**EXTINGUISHING MEDIA: FOAM, CO<sub>2</sub>, DRY CHEMICAL, WATER FOG**

**SPECIAL FIREFIGHTING PROCEDURES:**

Evacuate all unnecessary personnel. Use full protective equipment, including self-contained breathing apparatus.

**UNUSUAL FIRE HAZARDS:**

Product can splatter when heated. Dried film can burn. Vapors are heavier than air and may travel along ground to distant sources of ignition.

**Hazardous combustion by-products: see SECTION X**

===== **SECTION VI - ACCIDENTAL RELEASE MEASURES** =====

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:**

If odor is strong or spill is excessive, ventilate area, evacuate unnecessary personnel and wear full protective equipment. Dike and contain spill with inert material. Transfer liquid to containers for disposal or recovery. Prevent material from entering storm drains or sanitary sewers and open bodies of water.

**For specific information: see SECTION VIII**

===== **SECTION VII - HANDLING AND STORAGE** =====

**KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY!**

**PRECAUTIONS FOR SAFE HANDLING:**

Avoid contact with hot metal surfaces. Avoid breathing vapors and sanding or grinding dusts. Avoid contact with eyes and skin. Do not take internally. Use adequate methods of ventilation, respiratory and personal protective equipment. Follow label warnings until thoroughly cleaned or sent for disposal. Do not remove or deface label. Do not transfer to unlabeled container.

**CONDITIONS FOR SAFE STORAGE:**

Keep container closed when not in use and during transit. Do not store above 120 deg. F (50 deg. C). Keep in upright position and protect container from damage. Do not store where contact with incompatible material could occur, even during an accidental spill or release.

===== **SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION** =====

**COMPONENTS WITH WORKPLACE CONTROL PARAMETERS:**

- \* n-METHYL-2-PYRROLIDONE ACGIH TLV: Not Est. OSHA PEL: Not Est. Other: 19 ppm mist
- TRI-BUTYLETHYL PHOSPHATE ACGIH TLV: Not Est. OSHA PEL: Not Est.
- TRIETHYLAMINE ACGIH TLV: 1 ppm OSHA PEL: 25 ppm Other: 4.1 mg/m<sup>3</sup>(skin)
- PROPYLENE GLYCOL MONOMETHYL ETHER ACGIH TLV: 100 ppm OSHA PEL: Not Est. Other: 150 ppm STEL



**RESPIRATORY PROTECTION:**

Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's instructions for use.

**VENTILATION:**

USE ONLY WITH ADEQUATE VENTILATION.

**HAND PROTECTION:**

Wear impermeable gloves to prevent skin contact. Consult safety equipment supplier for specific recommendations of construction materials.

**EYE PROTECTION:**

Wear safety glasses designed to protect eyes against liquid splash and mists unless full facepiece respirator is worn. Note: Contact lenses may contribute to the severity of an eye injury and should not be worn when working with chemicals.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

Wear protective clothing to avoid skin contact with liquid or overspray.

**APPROPRIATE ENGINEERING CONTROLS:**

Eye washes and safety showers are recommended in the workplace. Wash hands after using and before eating, drinking or using tobacco products. Thoroughly clean contaminated clothing and shoes before reuse. Periodically monitor exposure levels to hazardous ingredients listed in section II and review permissible limits.

===== SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES =====

**BOILING RANGE:** 190 - 419  
**FLASH POINT:** 94  
**FLAMMABLE LIMITS IN AIR BY VOLUME-** LOWER: 1.2 UPPER: 13.8  
**MELTING POINT:** Not available  
**DENSITY:** 8.65-8.70 lb/gl  
**RELATIVE DENSITY:** No Data  
**V.O.C. (Coating):** 1.98-2.00 lb/gl 235-245 g/l  
**V.O.C. (Material):** 0.90-0.95 lb/gl 105-115 g/l (Emitted VOC)  
**LB HAP/LB SOLIDS** 0.00-0.03  
**LB VOC/LB SOLIDS** 0.3  
**SOLIDS % BY WEIGHT** 36-38  
**VAPOR DENSITY:** Heavier than air.  
**VAPOR PRESSURE:** See SECTION III  
**EVAPORATION RATE:** Slow (compared to n-butyl acetate)  
**SOLUBILITY IN WATER:** Appreciable  
**APPEARANCE AND ODOR:** Translucent liquid, mild odor.  
**VISCOSITY:** No Data

===== SECTION X - STABILITY AND REACTIVITY =====

**REACTIVITY:**

Will not occur.

**STABILITY:**

Stable

**POSSIBILITY OF HAZARDOUS REACTIONS:**

None known.

**CONDITIONS TO AVOID:**

High temperature and humidity, ignition sources and vapor build-up.

**INCOMPATIBILITY (MATERIALS TO AVOID):**

Strong Oxidizing agents Acids Alkalis Mineral Acids



**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:**

Carbon Monoxide Carbon Dioxide Hydrocarbons Nitrogen Oxides Ammonia Fumes Phosphorous Compounds

===== **SECTION XI - TOXICOLOGICAL INFORMATION** =====

**ACUTE TOXICITY:**

n-METHYL-2-PYRROLIDONE : LD50 Oral - Rat - 3,914 mg/kg  
LD50 Dermal - Rabbit - 8,000 mg/kg  
TRIETHYLAMINE: LD50 Oral - Rat - 730 mg/kg  
LC50 Inhalation - Rat - 4 h - 7.1 mg/l  
LD50 Dermal - Rabbit - 580 mg/kg

**PRIMARY ROUTE(S) OF EXPOSURE:** Inhalation, skin contact, ingestion.

**INHALATION:**

Vapors and mists cause severe irritation to nose, throat and lungs (burning, stinging, coughing). May cause headache, dizziness, nausea, weakness, shortness of breath and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Exposure to extremely high vapor concentrations may cause unconsciousness and asphyxiation.

**EYE CONTACT:**

Contact with liquid or vapors causes severe irritation (redness, watering, itching, stinging, blurred vision) and possible cornea damage.

**SKIN CONTACT:**

Contact causes irritation (dryness, itching, cracking, rash and swelling).

**SKIN ABSORPTION:**

May be absorbed through the skin in harmful amounts. Symptoms may include headache, dizziness, nausea, weakness, loss of coordination.

**SWALLOWING:**

Causes nausea, vomiting and diarrhea.

**CARCINOGENICITY:** Not Applicable

NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

**MEDICAL CONDITIONS POSSIBLY AGGRIVATED BY EXPOSURE:**

Respiratory tract irritation, nausea, eye disorders, skin disorders, sensitization to chemical substances.

===== **SECTION XII - ECOLOGICAL INFORMATION** =====

**TOXICITY:**

n-METHYL-2-PYRROLIDONE: Toxicity to fish LC50 - other fish - 4,000 mg/l - 96 h LC50 - Leuciscus idus (Golden orfe) - > 500 mg/l - 96 h  
Toxicity to daphnia and other aquatic invertebrates - EC50 - Daphnia magna (Water flea) - > 1,000 mg/l - 24 h  
Toxicity to bacteria LC50 - Bacteria - > 9,000 mg/l  
TRIETHYLAMINE: Toxicity to fish LC50 - Oryzias latipes (Orange-red killifish) - 24 mg/l - 96 h  
Toxicity to daphnia and other aquatic invertebrates LC50 - Daphnia dubia (water flea) - 17 mg/l - 48 h  
Toxicity to algae NOEC - Pseudokirchneriella subcapitata (green algae) - 1.1 mg/l - 72 h

===== **SECTION XIII - DISPOSAL CONSIDERATIONS** =====

**WASTE DISPOSAL METHODS:**

Waste material and empty containers must be disposed of in accordance with all local, state and federal environmental control regulations. Use only approved waste management facilities.

===== **SECTION XIV - TRANSPORT INFORMATION** =====



# Safety Data Sheet

GLITSA LATITUDE FINISH

2/24/2016

DOT (US): Not Regulated

Contact your supplier for specific information.

===== SECTION XV - REGULATORY INFORMATION =====

**COMMUNITY RIGHT TO KNOW LISTS**

**MASSACHUSETTS RIGHT TO KNOW:**

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE n-METHYL-2-PYRROLIDONE TRIETHYLAMINE

**PENNSYLVANIA RIGHT TO KNOW:**

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE n-METHYL-2-PYRROLIDONE TRIETHYLAMINE

**NEW JERSEY RIGHT TO KNOW:**

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE n-METHYL-2-PYRROLIDONE TRIETHYLAMINE

The following statement is required by California Proposition 65. Warning! This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

===== **DISCLAIMER** =====

DISCLAIMER: THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.