

Glitsa Poly

QuickDry Sealer

Specification Sheet

DESCRIPTION: Glitsa Poly Quick Dry Sealer is an oil-modified polyurethane sealer designed for residential and commercial hardwood floor applications. Glitsa Poly Quick Dry Sealer is designed for use under Glitsa Poly 500 Series or any Glitsa waterborne finish.

CHARACTERISTICS

Cast/Color:	Amber
Clarity:	Clear
Solids Weight:	38.4%
Viscosity (#2 Zahn):	22 seconds
Pounds/Gallon:	7.13
Flash point:	> 100° F.
Leveling:	Excellent
Drying Time:	@ 70° F., 50% Relative Humidity Touch: 2 hours Recoat: 4 hours
Coverage:	500 - 600 sq. ft. per gallon
VOC:	Max of 550 grams per liter

SURFACE PREPARATION

Natural wood floors:

- Sand to 100-120 grit using NWFA approved methods
- Screen with a 100-120 grit screen.
- Remove all sanding dust from the floor by thoroughly vacuuming and tack with a Glitsa Tack Mop.
- At this time a first coat of Glitsa Poly 500 or Glitsa Poly Quick Dry Sealer can be applied to the wood surface.

Stained floors:

- Sand to 100-120 grit using NWFA approved methods.
- Screen with a 100-120 grit screen.
- Remove all sanding dust from the floor by thoroughly vacuuming and tacking with a dry Glitsa Tack Mop.
- Refer to directions on Glitsa GoldSeal Stains for application procedures and dry times.
- Wood tone stained floors can be sealed with Glitsa Poly Quick Dry Sealer or Glitsa Poly 500.
- Glitsa Poly 500 is not recommended for pastel stained floors. For best results over pastel stained floors, use Glitsa TruSeal waterborne sealer and GlitsaMax waterborne finish.

APPLICATION

For best results, apply Glitsa Poly Quick Dry Sealer at temperatures between 60° - 70° F. (15.6 - 21.1° C.), and 40%-60% R.H. High humidity, or low temperatures will extend dry times. Make sure to have indirect ventilation while applying Glitsa Poly Quick Dry Sealer.

- Stir Glitsa Poly Quick Dry Sealer thoroughly.
- Apply Glitsa Poly Quick Dry Sealer by using a clean lambswool or synthetic applicator, or a lambswool roller.
- Start by pouring a 3"-5" puddle of Glitsa Poly Quick Dry Sealer with the grain of the wood, from wall to wall. Apply Glitsa Poly Quick Dry Sealer with the grain of the wood, from wall to wall.
- Use a cut-in pad or a T-bar to feather out turns.
- Maintain a 3" - 5" puddle at all times, as this will help to ensure even coverage, and a uniform final appearance.
- When Glitsa Poly Quick Dry Sealer has dried to the touch, ventilate premises, while maintaining temperatures of 60° - 70° F. (15.6° - 21.1° C.). Optimum air quality is achieved through aggressive ventilation.
- Once dry, abrade with a conditioning pad and 180 grit or finer sanding strips.
- For best results, vacuum carefully, and tack with water or mineral spirits using a Glitsa Tack Mop.
- A first coat of Glitsa Poly 500 may now be applied. Follow directions on finish label.
- Apply no more than two coats in a 24-hour period.

Clean equipment immediately after applying finish with mineral spirits and dispose of used solvent in accordance with local, state and federal regulations.

SHELF LIFE: One year in unopened container.

DISPOSAL: Dispose of unused contents in accordance with local, state and federal regulations.

CONTENTS: Mineral spirits (8052-41-3) and Trimethylbenzene (25551-13-7).



PLEASE READ MATERIAL SAFETY DATA SHEET
RUDD COMPANY, INC. • SEATTLE, WA 98107 • 1-800-444-7833
VISIT OUR WEB SITE AT WWW.GLITSA.COM