



GLITSA RETARDER

INSTRUCTIONS

For Industry Use Only

Read Material Safety Data Sheet and Label Precautions before using this product.

In hot dry climates, *Glitsa Retarder* may be added to Glitsa finishes to lengthen open time and aid flow. Note: Excess retarder will reduce the solid content of Glitsa finishes and lengthen dry time. Allow additional dry time when using *Glitsa Retarder*. *Glitsa Retarder* is available in quarts and gallons.

Directions for Use

Mix *Glitsa Retarder* thoroughly with the following Glitsa products only:

- **Gold Seal**
- **Gold Seal Lite Scent**
- **Bacca**
- **Glitsa Sealer**
- **Satin Sealer**

Use 1 - 3 oz. per gallon as needed; maximum 8 oz.

Precautions

Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe vapors or spray mists. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator during and after application.

Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.